



### WHITE PRINT PVC

The White Print PVC film can be printed on with any type of printing machine or method. It has a bubble free adhesive guaranteeing the white effect of the film.



SOLAR SCREEN® Warranty  
**3 YEARS**



Storage from -5°C to +40°C  
**3 YEARS**



REACH RoHS compliant  
**RESPECTED**

### WIDTHS AVAILABLE:

↔ **152 cm**

### TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	< 30 %
Visible light transmission	91 %

#### FRONT

Technology	Monomeric PVC
Thickness	100 µm
Finish	Glossy white

#### COMPATIBILITY

Surface(s)	Flat surface
Application type	Outdoor/indoor
Printing method	UV - UV gel - Aqueous print - Latex - Eco solvent - Solvent

#### DURABILITY

Outdoor resistance	5 years
Indoor resistance	8 years
Anti-scratch/hard coat	No

#### ADHESIVE


Type	Polyacrylate solvent
Performance	Removable

#### LINER

Type	Cardstock
Thickness	140µ

### CONSTRUCTION

1. White monomer PVC
2. Removable polyacrylate solvent adhesive
3. Protection release liner, disposable after installation



### MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.*