

### DATA JAMMER

Thanks to this polarizing film, create a blackout effect on your LCD or Plasma screens while preserving a perfect view through the glass.



SOLAR SCREEN® Warranty  
**2 YEARS**



Storage from -5°C to +40°C  
**1 YEARS**



REACH RoHS compliant  
**RESPECTED**

### WIDTHS AVAILABLE:

↔ **122 cm**

### TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	1 %
Visible light transmission	44 %
Reflection of external visible light	8 %
Reflection of internal visible light	9 %
Total solar energy rejected	30 %
Total solar energy rejected 2*	30 %
Solar ratio :	
Solar energy reflection	NC %
Solar energy absorption	NC %
Solar energy transmission	NC %
Reduction in Solar Glare	58 %
g-value	NC
u-value	NC
Shading coefficient	NC


Installation type :

Roll length	30,5 m
Film composition	PET + PVA
Thickness	132 μ

Colour from the outside :  
 TRANSPARENT

### CONSTRUCTION

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. PVA film
3. PS adhesive, polymerizes with glass within 15 days
4. Polarizing film



### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*\*

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	!

✓ Yes    ! Caution    ✗ Not recommended

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.

### MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film. Warning: special installation, see installation instruction sheet.

*Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.*